

TIMCO MITRE BOND ACTIVATOR (247951)

Page: 1

Compilation date: 26/03/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TIMCO MITRE BOND ACTIVATOR (247951)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: T. I. Midwood & Co. Ltd. TIMco House Green Lane Wardle Nantwich

- CW5 6BJ
- England

Tel: +44 (0)1829 261 111

Email: quality@TIMco.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1829 261 111

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements:	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated.
	H315: Causes skin irritation.
	H411: Toxic to aquatic life with long lasting effects.
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark
	GHS09: Environmental



TIMCO MITRE BOND ACTIVATOR (247951)

Page: 2

Precautionary statements: P211: Do not spray on an open flame or other ignition source.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P251: Do not pierce or burn, even after use.
P264: Wash hands thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective clothing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT MODIFIED NAPHTHA - NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-086-6	64741-84-0	-	Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	30-50%

PROPANE

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
BUTANE				
203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
ISOBUTANE				
200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%

N,N-DIMETHYL-P-TOLUIDINE

202-805-4	99-97-8	-	Acute Tox. 3: H331; Acute Tox. 3: H311;	<1%
			Acute Tox. 3: H301; STOT RE 2: H373;	
			Aquatic Chronic 3: H412	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

- Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
 - Ingestion: Wash out mouth with water. Consult a doctor.
 - Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

TIMCO MITRE BOND ACTIVATOR (247951)

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

TIMCO MITRE BOND ACTIVATOR (247951)

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

ea. The floor of the storage room must be
available in case of emergency.
5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol	
Colour:	Colourless	
Odour:	Characteristic odour	
Evaporation rate:	Fast	
Oxidising:	No data available.	
Solubility in water:	Not miscible	
Also soluble in:	Most organic solvents.	
Viscosity:	Non-viscous	
Boiling point/range°C:	No data available. Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available. upper:	No data available.
Flash point°C:	-40 Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	>300 Vapour pressure:	No data available.
Relative density:	No data available. pH:	Not applicable.
VOC g/l:	No data available.	

TIMCO MITRE BOND ACTIVATOR (247951)

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N,N-DIMETHYL-P-TOLUIDINE

IPR MUS LD50 212 mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

TIMCO MITRE BOND ACTIVATOR (247951)

Page: 6

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

TIMCO MITRE BOND ACTIVATOR (247951)

Page: 7

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other inform	nation
--------------	--------

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.
	H222: Extremely flammable aerosol.
	H224: Extremely flammable liquid and vapour.
	H229: Pressurised container: May burst if heated.
	H301: Toxic if swallowed.
	H304: May be fatal if swallowed and enters airways.
	H311: Toxic in contact with skin.
	H315: Causes skin irritation.
	H331: Toxic if inhaled.
	H373: May cause damage to organs ({{{0 message= <or affected,="" all="" if<="" organs="" state="" th=""></or>
	known> filter=(_)?ORGAN+}}) through prolonged or repeated exposure ({{{1
	message= <state conclusively="" exposure="" if="" is="" it="" no="" of="" of<="" other="" proven="" route="" routes="" th="" that=""></state>
	exposure cause the hazard> filter=(_)?EXP_ROUTE+}}}).
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.