

EVERBUILD MULTI-STICK

Colour	Product Code	Pack Size	Box Qty
Brilliant White	SKMULTISWE	350ml	12

Product Description

EVERBUILD MULTI-STICK based on hybrid polymer technology is the ultimate building adhesive, the first hybrid polymer grab adhesive especially created for the Trade, uniquely packed in a plastic 350ml cartridge. This superior adhesive has the ability to bond virtually anything to everything in both wet and dry conditions, and even underwater or in the rain. With incredible initial grab, high bonding strength, and almost limitless applications and other benefits, no tradesman should be without a tube of this next generation adhesive

Benefits

- Primerless adhesion to all common building substrates, porous and non-porous.
- Internal and External use.
- Fast curing.
- Solvent free.
- Virtually odourless.
- Low dirt pick up.
- Excellent break off and tooling.
- Waterproof.
- Weather resistant.
- UV resistant.
- Chemical resistant.
- Service temperature resistance (-50°C to +100°C).
- Suitable for use with glass, lead, polycarbonate, and acrylic sheets.

Areas for Use

- As a high quality nail replacement adhesive, even to damp surfaces.
- Bonding mirrors to most common substrates.
- Jointing cladding panels.
- Bonding difficult materials such as specialised polymer systems, metals and fibreglass
- Any application requiring high performance, durable bonding.
- Applications where resistance to chemical spillage is required (garage forecourts etc.)

Limitations

- Use on overhead applications – Always use in conjunction with mechanical fixings.
- Use in conjunction with mechanical fixings for glass block fitting or large mirrors (>0.5m² total area)
- For heavy items, provide temporary support until adhesive has dried.
- In areas of high UV; some darkening/discolouration may occur. This does not affect the performance.
- Overpaintability: check compatibility with specific paint first before over painting large areas.
- Do not use on polythene safety backed mirrors, polypropylene or Teflon.
- Do not use on surfaces that bleed oils or plasticizers
- It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for advice.
- Not for use as part of a glazing system.
- Not for use in aquarium manufacture.
- Not for use in conjunction with bitumen, or asphalt.
- Yellowing can occur in the dark.

Surface Preparation

The surfaces to be must be clean, dry and free from dust, grease and other contaminants. Improve adhesion by wiping surface with a suitable proprietary cleaner. Priming is generally not required, although we always advise testing small areas prior to use.

Application

Cut the tip of the cartridge taking care not to damage the thread. Fix nozzle, cut aperture to required width and apply with a standard sealant gun.

- Surfaces must be sound, clean, dry and free from dust, grease, loose material etc.
- Prime dusty surfaces with 501Bond® PVA+ diluted 1:4 with water and allow to dry.
- Apply using a standard sealant gun, cut tip of cartridge, apply nozzle and cut an opening to suite the required bead size.
- For bonding heavy items (Plasterboard/worktops/wall panels etc) apply adhesive all the way around the edge of the item (30-50mm from edge) and cover back with beads of adhesive at 300mm intervals. Alternatively, apply adhesive direct to battens and press into place.
- NOTE. *With heavy items, always provide temporary support until the adhesive dries.*
- For bonding lightweight items (covings, dado rails, skirting etc) apply adhesive to back of item in one or two continuous beads and press immediately into place.
- Where gap filling is required, mark the areas where there is a large gap and apply a thicker bead to these areas.
- In all cases, clean up excess adhesive immediately with a cloth/white spirits

Specific Data

TEST	RESULT
Skinning time:	20 – 40 mins
Cure time	1-2mm per 24 hours
Hardness Shore A	50-60
Service temperature resistance	-50°C to + 100°C
Application temperature resistance	+5°C to + 35°C
Specific gravity	1.7 g/cm ³
Cleaning	Uncured sealant white spirit.
Sagging (ISO7390)	Nil

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store in cool dry conditions away from direct sunlight between +5°C and +25°C. Storage outside these parameters will dramatically reduce the shelf life.

Shelf Life

Use 12 months from date of manufacture.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance

with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.